



| | | |
|-----------------------------------|---|--|
| Product Image | | |
| Part Number | 909020053 – PAC 520 Input Controller - DIN Mount | 909020051 PAC 520 Input Controller – Metal Cased |
| Dimensions | W 180 x H 125 x D 40mm | W 150 x H 220 x D 40mm |
| Operating Temperature | -10°C to +55°C | |
| Operating Humidity | 0% to 85% Relative Humidity | |
| Controller Inputs | 20 configurable inputs: <ul style="list-style-type: none"> • Normally Open, Normally Closed and 2, 3 or 4 state • 5Amp Relays @ 30 V DC | |
| Controller Outputs | 2 configurable outputs: <ul style="list-style-type: none"> • Latched, Momentary, Toggled and Pulsed • 5Amp Relays @ 30 V DC | |
| Additional Connections | 1 x tamper alarm input 1 x override input 1 x RS-485 input | |
| Auxiliary power outputs | 2 x Polyfused 200mAmp Auxiliary voltage output | |
| Configuration | via PC with PAC Access Central software | |
| Connection to PAC 512 | RS-485 | |
| Maximum Distance to PAC512 | 1000m | |
| Power input | 10.5 – 28 V DC 115mA @ 10.5 V DC 45mA @ 28 V DC | |
| Warranty | 5 years against electronic failure | |
| Standards Compliance | CE, RoHS & WEEE compliant | |



Date of print/release: (September 2020)

This document is provided by STANLEY Security or its affiliates ("STANLEY") for general information purposes only. STANLEY warrant the accuracy of the data as at the date of print/release, but it may be subject to change after such date. STANLEY will not be responsible for any loss or damage that may arise from reliance thereof. Copyright © STANLEY Security 2020. PAC, GDx and 3xLOGIC are the trade marks of STANLEY Security, Stanley Black & Decker, Inc., or their affiliates.

Ordering Information:

PAC Access Control, 1 Park Gate Close,
 Bredbury, Stockport, Cheshire, SK6 2SZ
 customerservices@pacgdx.com | +44 (0) 161 406 3400
 www.pacgdx.com