

READERS | K2010 153KHz Proximity Key Fob

Overview

The K2010 Key Fob is compatible with the entire Stanley GS3, Readykey K2000-series and Easikey reader and credential range. Unobtrusive and compact it fits on a key ring and can be easily incorporated into any existing Stanley PAC Access, Readykey for Windows or PAC Vision security management software, and is often used where photo ID is not required.

As an alternative to the traditional mechanical key, millions of Stanley PAC proximity cards and fobs are used by people as an easy and reliable means of gaining access to their places of work and other secured access points e.g. car park barriers and turnstiles.

The passive proximity technology in the key fob requires no batteries or physical contact with the reader; this helps assure that the tokens are virtually wear-free and will provide years of service with no maintenance backed by a lifetime warranty. Robust, world-class construction combined with advanced technology and a pre-programmed unique identification number without site codes, makes programming easy and copying almost impossible.

Together with the access control system, the key fob enables a user's movements to be monitored and the building protected. The Key Fob need only be held near the proximity door reader for the code to be read and access granted or denied within 0.5 of a second. In the event that the token is lost or stolen, it can easily be replaced and the lost token access privileges, simply and instantly revoked.

Key Features

- Offers fast and convenient access
- Small and convenient
- Rugged and durable 'washing machine tough' design
- Versatile, easily attached to a keyring, badge clip, chain or carried in pocket or handbag
- Universal compatibility with all Stanley PAC GS3 and Readykey K2000-series readers
- Proven and reliable technology
- High security, offering over a billion unique code combinations.
Card numbers are embedded and tracked in the manufacturing process ensuring that card numbers are never duplicated.
- Double sealed and ultra-sonic welded ABS construction
- Proven, Reliable 153KHz Technology
- Long life, passive no battery design
- Compatible replacement for the EK71 Easikey Key Fob
- Lifetime Warranty



FEATURES AND SPECIFICATIONS CHART

	K2010 Key Fob
Description	Uniquely coded, 153KHz, proximity token
ID Technology	Readykey/PAC K3010 - 125KHz
Dimensions	H: 2.40 in. L: 1.10 in. D: 0.20 in.
Weight	0.32 oz. nominal
Operating Temperature	-18° to 131°F
Token Outer Construction	Double sealed ultrasonic welded ABS plastic
Token Inner Construction	RF core fully encapsulated in epoxy
Finish Front	Black matt plastic with PAC logo cap
Finish Rear	Black matt plastic
Warranty	Limited Lifetime warranty against defects in materials and workmanship .
Ordering Information Stanley PAC Part Number (Supplied in pack of 10)	75-K2010 - Proximity Key Fob



CREDENTIAL READ RANGE

	Stanley Key Fob	Stanley ISO Card
Standard Reader	Up to 4.7 in.	Up to 7 in.

PAC CREDENTIALS



K2010
OLD STYLE



K2010



EK71



K2011

